

Product specification

Name : LED machine work light


Model : M3 Series



Products introduce:

1. Delicate structure, simple and beautiful, competitive price
2. The radiating of light is good, to insure the life spans of products
3. Imported light from Taiwan, china famous power
4. Fixed by screw base, universal with traditional light, easy install
5. The flex of hose is good, can adjustable any angle of illumination

Products photo and size photo:



Specification Data:

Mode No.	Input Volt	Output Volt	CCT
ONN-M3S-B1	AC/DC 24V	AC/DC 24±2V	5500-6000K
ONN-M3S-B2	AC/DC 24V	AC/DC 24±2V	4000-4500K
ONN-M3S-B3	AC/DC 24V	AC/DC 24±2V	2800-3200K
ONN-M3S-C1	AC220V (50/60Hz)	AC100-240V (50/60Hz)	5500-6000K
ONN-M3S-C2	AC220V (50/60Hz)	AC100-240V (50/60Hz)	4000-4500K
ONN-M3S-C3	AC220V (50/60Hz)	AC100-240V (50/60Hz)	2800-3200K



Length of Cable	0.75M open wire, without plug. 24v: red/white wire; 100-240v: brown/blue/yellow wire.		
Mounting Method	Fixed base (Screws prepared by customer)		
Consumed Power	5W		
Input Current	(24V) 420mA / (220V) 50mA		
Flux	400-420Lm		
Life span	50 000H	Protection Level	IP30
Luminous Efficiency	70-75Lm/W	CRI	70Ra
Driver	Non-isolated	PF	≥ 0.5
Surface temperature	< 60°C	View Angle	40°

Environmental Requirements:


Working temperature:	-20~45°C
Save temperature:	10~60°C
Working humidity:	10~90%
Save humidity:	10~90%

Picture of light distribution curve:

配光曲线



The table of average illumination:




Packing:

Packing material	cartons
Size of products (MM)	585
N/W of one light (Kg)	0.58
G/W of total cartons(Kg)	16
Qty in carton(PCS)	20
Size of inner box (L*W*H) mm	610*85*85
Size of outer carton (L*W*H) mm	620*380*460

Installation:

Fixed by base:


- 1) Make a hole in specify place, diameter of hole is 6mm.
- 2) Fixed by screw, and after finished install, adjustable the angle as you need. (like photo in right).



220V cable



24V cable



L: live line; N: Neutral line
